

|  | Section 1 Material-equipment for elder and health  |  |
|--|--|--|
| Elevator   | By "ARTICO" model S15 for house model EA-234 and EA-235 only   |  |
| Air ventilation system   | <b>PM 2.5</b> prevention and clean air ventilation equipment by <b>PD Fresh Airflow</b> model <b>Fresh II</b> , wall mounted in the bedrooms and bathrooms except maid room-maid bathroom (if any)   |  |
| Elder room floor   | Shock absorb Safety Floor – PVC type, by KRONOTEX with PVC floor skirt   |  |
| Entrance ramp  | As specified in drawing (if any)   |  |
| Elder bathroom door  | White <b>Wood Plastic Composite (WPC)</b> door, hanging sliding type, <b>1.00 meter</b> wide. With groov pattern ( <b>MN80-P01G03, MN80-P01G05</b> or <b>MN80-P01G08</b> to be chose later) and sliding rail, equipment and white rail cover by MOHNE' |  |
| Elder Bathroom (if any)  | "AMERICAN STANDARD" or COTTO" (White color) or equal (as specified by company)   |  |
| Water closet   | Model: <b>COTTO For All SC5622 with white seat C9251</b> and equipment<br>Cleaning spray model: <b>A-4700A-WT</b> with stop valve mode <b>STD A-4401</b>   |  |
| Wash basin   | Model: COTTO For All SC00537   |  |
| Mirror   | Model: MZ901#WH  |  |
| Soap holder  | Model: American Standard <b>TF-9402</b>  |  |
| Tissue holder  | Model: American Standard <b>TF-9411</b>  |  |
| Towel bar  | Model: American Standard <b>TF-9485</b>  |  |
| Wall mounted faucet for shower                                     | Model: American Standard <b>NEO MODERN MONO A-0726-10-A</b><br>with chromium shower set  |  |
| Wash basin faucet  | Model: American Standard STD NEO MODERN MONO A-0706-10   |  |
| Wall mounted faucet  | Model: American Standard STD WINSTON FFAST602-0T0500BT0  |  |
| Bathroom floor drain   | Model: <b>CT699Z1</b> by COTTO (size 100 cm.)  |  |
| Safety accessory for Elder<br>bathroom                             | Handrail model: COTTO HANDICARE CT752#SA<br>Foldable support arm model: COTTO CT0190   |  |
| Section 2 Material-equipment for energy saving and heat insulation |  |  |
| Solar water heater   | <b>Capacity 160 litres with hot water piping</b> (Pimaflex) for <b>2 bathrooms upstairs</b> for wash basin and shower, 2 for each bathroom.  |  |



| Heat prevention beneath the roof                  | <ul> <li>3 inches thick insulator by "STAY COOL": Premium placed on ceiling beneath upper and lower roof level (except garage, upper/ lower terrace and external ceiling).</li> <li>For the concrete roof or concrete floor (Concreye slab), 6 inches thick "STAY COOL": Premium is used.</li> </ul> |
|---|--|
| Sanitary ware<br>(water saving)                   | "AMERICAN STANDARD" or COTTO" (White color) or equal (as specified by company)   |
| Water closet for master<br>bathroom               | Model: TF-2019-WT9 , with electric bidet seat  |
| Water closet for general bathroom                 | Model: <b>STD MILANO TF-2327SC-WT-0</b> with accessories<br>Cleaning spray model: <b>A-4700A-WT</b> with chromium stop valve model <b>STD A-4401</b>   |
| Roof tile   | In case of Insulated Roof, the <b>Ceramic Metal Roof : Snaplock</b> – premium color by <b>PD</b><br><b>INSULATED</b> (choose the color later) will be used.  |
| Wall material                                     | General wall : <b>10 cm. thick</b> Autoclave concrete with plastering and skim coat<br>Decorated wall (if any) ; <b>7 cm. thick</b> Autoclave concrete with plastering and skim coat   |
| Section 3 Environment friendly material-equipment |  |
| Flooring material                                 | General first floor and upper floor - <b>12 mm.</b> thick laminated floor by <b>"KRONOTEX": Robusto</b> or <b>"INOVAR": Exquizite Max Pro</b> with PVC floor skirt.  |
| Wooden Stair Set                                  | A set of Engineered Wood by ACON color coated from the factory   |
| Stair tread                                       | Size 300x30 mm.  |
| Riser   | Size 200x20 mm.  |
| Handrail  | Size 100x50 mm.  |
| Post  | Size 125x125 mm.   |
| Baluster  | Size 50x50 mm.   |
| Landing   | 30 mm. thick, 2 pieces (V groove connect)  |
| Eave ceiling                                      | Wood Plastic Composite (WPC) by PD WOOD by Maxis Wood model QB-003 Teak color or equal with Zinc galvanized studs#26.  |
| Decorated wall (If any)                           | In case of fiber cement decorated wall, use "SCG" or "CONWOOD" or Wood Plastic<br>Composite (WPC) - PD WOOD by Maxis Wood model QB-003 teak color or as drawing<br>specified   |



| Interior Door   |  |
|---|--|
| General interior door/<br>Bedroom/ Storage room (If<br>any)                             | Laminated Wood Plastic Composite (WPC) door and white wood pattern film coated Wood<br>Plastic Composite (WPC) door frame by "PD WOOD" : L-WPC-004-006 (choose color later)                            |
| Bathroom door   | White Wood Plastic Composite (WPC) door and white wood pattern film coated Wood Plastic Composite (WPC) door frame by "PD WOOD" model C-WPC-001-003  |
| Maid bathroom door  | White Wood Plastic Composite (WPC) door and white wood pattern film coated Wood Plastic Composite (WPC) door frame by "PD WOOD" model C-WPC-001-003  |
| Door for storage room under<br>stair (if any) / Door for<br>electric control unit panel | White PVC door panel with louver   |
| Door for kitchen/ garage<br>(open to exterior)  | White <b>Wood Plastic Composite (WPC)</b> door and white wood pattern film coated Wood Plastic Composite (WPC) door frame with steel structure by " <b>PD WOOD</b> " model <b>C1-WPC-008, 011, 012</b> |
| Facia   | Synthetic wood "Eave Plus" or equal  |
| Treatment Tank  | Fiberglass tank by "DOS": ST-21/GY or "PP": Ecotank or equal (underground type).   |
| Grease trap Tank  | Fiberglass tank by "DOS": GT-09/BK-40 or "PP":GT-30UG (underground type).  |
|   | Section 4 Innovation and technology material-equipment   |
| Concrete structure  |  |
| Footing/Column /Beam<br>/Staircase/ bathroom tray/<br>Parking floor                     | <b>Prefabrication structure with Multi Joint Lock System</b> . Some parts of structure are cast-in-<br>place as engineer specified.  |
| General concrete floor  | Prestressed concrete plank by <b>D-CON</b> or <b>PCM</b> or equal Some parts of structure are cast-in-<br>place as engineer specified.   |
| Exterior doors/windows  | by TOSTEM  |
| Door to Terrace / Balcony/<br>main entrance   | <b>Anodized</b> color aluminum by <b>"TOSTEM" : ATIS</b> or as manufacturer specific or equal with 4.5 mm. thick clear green glass   |
| General Window  | <b>Anodized</b> color aluminum by <b>"TOSTEM" : ATIS</b> or as manufacturer specific or equal with 4.5 mm. thick clear green glass.  |



| (                          |   |  |
|----------------------------|---|--|
| Bathroom window            | <b>Anodized</b> color aluminum by <b>"TOSTEM" : ATIS</b> or as manufacturer specific or equal with 4.5 mm. thick frosted glass.   |  |
| Adjustable Louver (if any) | <b>Anodized</b> color aluminum by <b>"TOSTEM" : ATIS</b> or as manufacturer specific or equal with 4.5 mm. thick clear green glass.   |  |
| Plastering material        | Mortar cement by "SCG", "INSEE", "TPI", "SINGHA MORTAR" or equal with skim coat. For exterior, wall protective formula mortar "PD Mortar Plus" and fiberglass mesh with skim coat is used.  |  |
| Roof Truss                 | Alu-zinc (AZ-150) or SuperDyma coated high strength steel structure with screw and nut system as engineer specified.  |  |
| Interior clear water pipe  | Pimaflex Mutipipe by PIMATEC  |  |
| Interior clear water pipe  | 25x2.5 mm. (internal dia. 20 mm.) for main pipe<br>20x2.25 mm. (internal dia. 15.5 mm.) for branch pipe<br>16x2.0 mm. (internal dia 12 mm.) for hot water pipe  |  |
|                            | Section 5 General material – equipment  |  |
| Piling                     | Bangkok area and surrounding area         One storey house pre-stressed concrete pile I-22 not exceed 12.00 m. long (2 piles welded connection)         Two storey house pre-stressed concrete pile I-22 not exceed 18.00 m. long (2 piles welded connection).         Three storey house pre-stressed concrete pile I-22 not exceed 21.00 m. long (02 piles welded connection)         In case driven pile cannot be used, drilled pile as engineer specified is used (extra cost)         Provincial area (stiff soil),         One storey house pre-stressed concrete solid square pile 22 X 22 cm., length not exceed 10.00 m. is used.         Two -3 storey house pre-stressed concrete solid square pile 22x22 cm. length not exceed 10.00 m. is used. |  |
| Floor of washing area      | Reinforced concrete slab on ground as engineer specified.   |  |
| Entrance pavement          | N/A   |  |
| Concrete                   | Ready mixed concrete by SCG, INSEE, TPI   |  |



| Floor Level   |   |
|---|---|
| First floor level                                     | <b>0.80 meter high from the ground</b> or as specified in the drawing (In case of multilevel floor).                    |
| Flooring Material                                     |   |
| Master bathroom floor                                 | Ceramic tile "A" grade (price not exceed 600 baht/sq.m.).   |
| General bathroom floor                                | Ceramic tile "A" grade (price not exceed 350 baht/sq.m.).   |
| Main entrance terrace                                 | Ceramic tile "A" grade (price not exceed 550 baht/sq.m)   |
| Kitchen floor   | Ceramic tile "A" grade (price not exceed 350 baht/sq.m.) with PVC floor skirt.  |
| Terrace /Balcony floor                                | Ceramic tile "A" grade (price not exceed 350 baht/sq.m.).   |
| Waterproofing system for terrace/balcony/toilet floor | the paint type waterproofing system, <b>TOA Cement Waterproof</b> with <b>fiberglass mesh</b> or equal will be applied. |
| Maid Room floor                                       | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Maid bathroom floor                                   | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Storage room floor                                    | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Laundry floor (If any)                                | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Parking floor   | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Washing area  | Ceramic tile "A" grade (price not exceed 200 baht/sq.m.).   |
| Footpath (If any)                                     | Coarse polished cement.   |
| Wall Finishing  |   |
| Master bathroom wall                                  | Ceramic tile "A" grade (price not exceed 600 baht/sq.m.) height not exceed 2.40 m.                                      |
| General bathroom wall                                 | Ceramic tile "A" grade (price not exceed 300 baht/sq.m) height not exceed 2.40 m.                                       |
| Maid bathroom wall                                    | Ceramic tile "A" grade (price not exceed 200 baht/sq. m) height not exceed 2.40 m.                                      |
| Decorated wall (If any)                               | Natural color granite " <b>BEZEN</b> " 2"x9" (price not exceed 800 baht/sq.m.) or equal, spaced grooves                 |



| Ceiling                                     |   |
|---|---|
| General interior ceiling                    | Beveled edge gypsum board <b>9 mm. thick</b> by <b>"SCG"</b> or <b>"GYPMANTECH"</b> with galvanized metal studs#26. 1 set of 60x60 cm. instant service access on the second-floor ceiling.  |
| Exterior ceiling<br>(Balcony/Garage)        | Beveled edge moisture resistant gypsum <b>9 mm. thick</b> by "SCG" or "GYPMANTECH". with galvanized metal studs#26  |
| Ceiling for bathroom                        | Beveled edge moisture resistant gypsum board <b>9 mm. thick</b> by "SCG" or "GYPMANTECH" with galvanized metal studs #26  |
| Roof tile                                   | Concrete roof tile model Adamas Tile, chalet shake or smooth tile model with Platinum color<br>coated (Sunny red, Brightly brown) with "Dry ridge system", stainless #24 for valley rafter.<br>In case of Metal sheet roof, 0.47 mm. thick metal sheet, Alu-zinc color, with 5 mm. PE Foam<br>insulation will be applied.<br>In case of polished concrete roof, the paint type waterproofing system, TOA PU Waterproof<br>with fiberglass mesh or equal will be applied.<br>In case of Shingle Roof, use the Double layer type (the color chosen later) with equipment<br>from manufacturer |
| Facia                                       | In case of Metal Sheet roof, the flashing is the same color as the roof.  |
| Railing                                     | Vinyl railing by "WINDSOR" as specified drawing (steel/ stainless).   |
| Door and Window Accessor                    | ies   |
| Handle / Lock set for<br>general doors      | Stainless steel mortise lock set by "MATURE" model Premium MSL-018 (silver hairline) or equal with stainless steel door stopper   |
| Hinge for general doors /<br>bathroom doors | Stainless steel butterfly hinge" by "MATURE": MH-S4325 HS2BB or equal, 4 pieces/door  |
| Lock set for bathroom                       | Stainless steel knob by "MATURE": MK-001-BK-SS or equal with stainless steel door stopper   |
| Lock set for maid bathroom                  | Stainless steel knob by "MATURE": MK-001-BK-SS or equal with stainless steel door stopper   |
| Adjustable louver (If any)                  | By " <b>TOSTEM</b> " or equal   |
| Hung type sliding door                      | By "HAFELE" or equal  |
| Sanitary ware                               | "AMERICAN STANDARD" or COTTO" (White color) or equal (as specified by company)  |
| Water closet for maid<br>bathroom           | Model: STD WINSTON II TF-2695SCW-WT-0 with accessories. Cleaning spray model STD AS<br>BASIC F75006-WTADY with chromium stop valve model STD A-4401   |



| Wash basin                          | General bathroom model: <b>WP-F507-WT, under the counter type</b><br>Maid bathroom model: <b>STD WINSTON II TF-0979-WT-O</b> , wall hung type   |
|-------------------------------------|---|
| Bathroom counter                    | General bathroom counter <b>topped with granite stone</b> (Engineer grey, Chinese pink, white tone or equal), counter edge topped with ceramic tile "A" grade same as the wall.   |
| Bathtub (only 1 master<br>bathroom) | Model: <b>TF-8151</b> with wall mounted type mix faucet and shower set model: <b>NEO MODERN A-0711-200</b> with hot water pipe.   |
| Urinal                              | Model: WP-6747 NEO MODERN with automatic electronic flush valve accessories model: A-<br>8014AC-WT (in 1 bathroom downstairs)   |
| Mirror                              | Model: LV02 / model GH-805 for maid bathroom)   |
| Soap holder                         | Model: TF-9402 /model TF-9000 for maid bathroom   |
| Tissue holder                       | Model: TF-9411 /model TF-9011 for maid bathroom   |
| Towel bar                           | Model: TF-9485 /model TF-9085 for maid bathroom   |
| Wall mounted faucet for shower      | General bathroom model: <b>NEO MODERN MONO A-0726-10-A</b> with chromium shower set<br>Bathroom with hot water piping model: <b>NEO MODERN A-0712-300</b> with chromium shower set<br>Maid bathroom model: <b>F46103-CHADYHS</b> with stop valve model <b>AS BASIC F21033-CHADY</b> |
| Wash basin faucet                   | Master bathroom, bathroom with hot water piping model: <b>STD NEO MODERN A-0701-100</b> (2 points in total)<br>General bathroom model: <b>STD NEO MODERN MONO A-0706-10</b><br>Maid bathroom model: <b>STD WINSTON FFAST 601-1T1500BT0</b>  |
| Wall mounted faucet                 | General bathroom and maid bathroom model: <b>STD WINSTON FFAST602-0T0500BT0</b> (one in each bathroom)  |
| Shelf                               | Model: <b>TF-9075</b> for maid bathroom   |
| Bathroom floor drain                | 2" diameter odor trap floor drain (square type) model: <b>STD A-8200-N</b> chromium color, 2 for each bathroom.   |
| Water                               | Comply with Standard of Metropolitan Water Authority or Provincial Water Work<br>Authority. PVC pipes by SCG or THAI PIPE   |
| Clear water pipe                    | <sup>3</sup> ⁄ <sub>4</sub> " dia. <b>PVC pipe</b> (class 13.5) for main pipe from building to meter, <b>length not exceed 30.00</b><br><b>m</b> . with ball valve, metal hand, separating for each floor.  |



| Waste water/ Drain           | 4" dia. PVC pipe (class 8.5) for sewage pipe. 2" dia. PVC (class 8.5) for drainage pipe and 3" dia. For main pipe (class 8.5)  |
|------------------------------|--|
| Ventilation pipe             | 1" dia. PVC pipe (class 5.0 )  |
| Rain water drainage          | 2" dia. PVC pipe for branch rain water pipe and <b>3" dia. for main water pipe</b> (class 8.5). Skull shape stainless steel floor drain for balcony or concrete slap roof. |
| Sanitary System              |  |
| Drainage pipe                | Asbestos cement pipe dia. 8" to public drain (Not exceed 20.00 m. long from the house).  |
| Manhole                      | 30x40 cm. precast manhole every 6.00 m. interval and every bends or corners.   |
| Electrical System            | Comply with Standard of Metropolitan Electricity or Provincial Electricity Authority   |
| Main income wiring           | Single copper wiring PVC insulated (KV-CV#35 sq.mm.) The length from wall to meter not exceed 30.00 m (put in PE conduit dia. 2" underground).                             |
| Main income telephone wiring | Four cores wiring not exceed 30.00 m. from meter to the house put in PE conduit $\frac{1}{2}$ " underground.   |
| Internal wiring              | Single copper wiring with PVC insulated with yellow PVC conduit in wall or on ceiling.   |
| Air condition wiring         | 1 point at Master Bedroom  |
| Control panel                | 15 Amps. <b>19 circuit</b> breaker by <b>"HACO": HD-S119</b> or equal with Residual Current Device (RCD).  |
| Lighting switch              | Wall mounted lighting switch by "HACO": Primo PR-F001-3 / PR-FS111/L (2 way type switch only at stair hall) 1 for each room and 2 for Master Bedroom.                      |
| Receptacle                   | Wall mounted receptacle by "HACO": Primo PR-E233, 2 for each room and 3 for reception room (except storage/bathroom).  |
| TV / Telephone outlet        | Wall mounted TV/Telephone outlet by "HACO": Primo PR-T075 (TV) / PR-R024 (telephone) 3 for each.   |
| Emergency light              | 1 set of twin LED lamp head emergency light  |
| Luminaire                    | Provided by the owner  |
| Electricity and Water Meter  |  |
| Permanent electric meter     | 15 Amps, Fee covered by company. (Exclude the service area extension fee)  |



| Permanent water meter              | 3/4" Diameter, Fee covered by company. (Exclude the service area extension fee)   |
|------------------------------------|---|
| Painting                           | Ву ТОА  |
| External wall                      | External acrylic paint "TOA": Supershield or equal,1 primer and 2 final coated  |
| Internal wall                      | Internal acrylic paint "TOA": Supershield Duraclean or equal,1 primer and 2 final coated  |
| Steel surface                      | Emulsion paint <b>"TOA": Glipton</b> or equal 1 primer and 2 final coated   |
| Facia/Fiber Cement Board           | External acrylic paint <b>"TOA": Supershield</b> or equal,1 primer and 2 final coated   |
| Others                             |   |
| Termite protection system          | <sup>1</sup> / <sub>2</sub> " PVC Piping (class 13.5) by SCG or Thai Pipe with springer system, for termite chemical treatment, are provided by company. <b>The owner responds for termite service provider</b> . |
| Tile adhesive                      | Glue cement by Singha, Crocodile, Tiger or Waber  |
| Section 6 Warranty and maintenance |   |
| Structure                          | 20 years warranty for the structure   |
| General work                       | <b>2 years</b> warranty for general work<br>Exclude natural depreciation of materials due to long used and misused.   |

**Remarks:** The company reserves the right to change the list if needed but the price of the materials is not less than that stated above. The cost of the construction does not include:

- Old building demolition Interior decoration and garden Air conditioner system.
- Water drainage outside the construction site. Mosquito net, door and window steel bars, rain gutter